

Low Vibration & Low Noise

(vibration value = vector sum of 3 axes)

Comparison of Vibration level

5.7m/s²

3.1m/s² 7.6m/s²

Vibration level of BO4556 is less than half

Comparison of Noise level



Noise level of three BO4556s is equal









Plastic Carrying Case Part No. 824806-0



Paper dust bag holder Part No. 193932-9

Paper bag (5pcs./set) Part No. 193712-3

Dust bag assembly Part No. 166078-4



Abrasive paper For Model: BO4555, BO4556 Paper Size: 114mm x 140mm


Punch plate Part No. 450066-4



	Grit	per pkg.	Part No.	
ı	60	10	794216-460	
	80	10	794469-5	
	100	10	794215-660	
	150	10	794214-8	

Finishing Sander

BO4555 / BO4556 / BO4565 / BO4566





Carrying case (BO4555 / BO4556 / BO4565)















		BO4555	BO4556	BO4565	BO4566
Continuous rating Input		200W	200W	200W	200W
Pad size		112 x 102mm (4-3/8" x 4")	112 x 102mm (4-3/8" x 4")	112 x 190mm (4-3/8" x 7-1/2")	100 x 164mm (3-15/16" x 6-1/2")
Abrasive paper size	Hook &loop:	114 x 102mm (4-1/2" x 4")	-	114 x 102mm (4-1/2" x 4")	102 x 166mm (4" x 6-1/2")
	Clamp:	114 x 140mm (4-1/2" x 5-1/2")	114 x 140mm (4-1/2" x 5-1/2")	-	-
	Triangle:	-	-	96 x 96 x 96mm (3-3/4" x 3-3/4" x 3-3/4")	-
Dimensions		131x 112 x 142mm	131x 112 x 141mm	219 x 112 x 139mm	197 x 100 x 137mm
(L x W x H)		(5-1/8" x 4-3/8" x 5-5/8")	(5-1/8" x 4-3/8" x 5-9/16")	(8-5/8" x 4-3/8" x 5-1/2")	(7-3/4" x 3-15/16" x 5-3/8")
Orbits per minute (opm)		14,000	14,000	14,000	14,000
Net weight		1.1kg (2.4lbs)	1.1kg (2.4lbs)	1.1kg (2.4lbs)	1.1kg (2.4lbs)
Power supply cord		2.0m (6.6ft)	2.0m (6.6ft)	2.0m (6.6ft)	2.0m (6.6ft)
Standard Equipn	nent	Abrasive Paper set, Dust Bag, Punch plate	Abrasive Paper set, Dust Bag, Punch plate	Abrasive Paper set, Dust Bag	Dust Bag

Items of standard equipment and specifications may differ by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan



Freestyle Sanding

Smooth Sanding by Powerful 200w motor

Comfortable Sanding by Low Noise and Low Vibration

Clean Sanding by High Dust Extraction




Freestyle Sanding

Ergonomically Contoured Grip with Non-Skid Elastomer Covered Surface.

Fits your palm perfectly. Also provides more control and comfort while minimizing hand fatigue and pain when gripping the tool from the side.







Slimmer design allows secure grip with all the fingers relaxed.



Ergonomic shape of the tool head designed based on research of palm sizes.



Low Vibration: 3.1m/s² (loaded)*
Dual counterweight balancing system
for reduced vibration.

Low noise 81dB (loaded)*

by aluminum foot and counterweight *In case of using BO4556



Rigid aluminum foot with dust-proof sponge for longer tool life Enhanced Foot



High Dust Extraction

Dust is extracted through 6-hole under Pad and collected into Dust Bag. Also, instead of Dust Bag, Makita Vacuum Cleaner can be connected to the tool using Adapter.



Easy-to-Operate Paper Clamp (BO4555 and BO4556) Easy installation/removal of paper with rolled clamper's edges



•Conveniently located ON / OFF Switch for One-Handed Operation.

•Rubber Switch Cover prevents ingress of dust.